DATASHEET

Three Phase Induction Motor	Drawing No.	
SKU:	GB35430051T001	
Type:	**OMT4-IE3 100L2-4 3kW 400/690V 50Hz**	

Identification

Frame:	100	mm	Insulation Class:	F	
Output:	3	kW	Temperature Rise:	80K	
Frequency:	50	Hz	Service Factor:	1,0	
Poles:	4	P	Duty:	S1	
Rated Speed:	1455	rpm	Ambient Temperature:	-20~40	
Slip:	3,0	%	Altitude:	1000m	
Rated Voltage:	400 / 690	V	Protection Degree:	IP55	
Connection:	Δ/Y		Cooling:	IC411	
Rated Current:	6,0 / 3,5	A	Mounting:	B3;B35;V1;B5;B14S;B14L;B34S;B34L	
Rotor Voltage:			Vibration:	1,6 mm/s	
Connection:			Approx. Weight:	32	kg
Rotor Current:			Moment of Inertia:	0,01011575	kg/m2
Locked Rotor Current:	760	%	Noise Level（Lp）:	67	dB(A)
No Load Current:			Direction of Rotation:	BOTH	
Rated Torque:	19,7	Nm	Starting Method:	DIRECT ON LINE	
Locked Rotor Torque:	230	%	Coupling:	DIRECT	
Breakdown Torque:	230	%	**Load Type:**	PARABOLIC CURVE	
Nominal Power Loses	13,90	%			

Performance

Output:	50%	75%	100%
Efficiency(%):	85,2	87,9	87,8
Power Factor:	0,70	0,78	0,82

Bearing Information

	DE	NDE
Bearing:	6206 2RZ C3	6206 2RZ C3
Regreasing int.(h):		
Grease amount(g)		
Grease-PolyrexEM		

Accessories

3x PTC 150°C

Notes

Standards

Specification:	IEC60034-1/GB755
Test:	IEC60034-2/GB/T1032
Noise:	IEC60034-9/GB10069.3
Vibration:	IEC60034-14/GB10068

Edition

Performed	Checked	Date

PRELIMINARY DOCUMENT

Item	Changes	Performed	Checked	Date

There may be differences between rating plate and calculated values.