SHANGHAI TOP MOTOR CO., LTD.

Technical Data Sheet

General data		
Frame size	71	
Housing material	Aluminum	
Install model	According to the standard	
Type of feet	Removable feet	
Net weight	6.25 kg	
Insulation class	F *H*	(Standard) *(Optional)*
Protection degree	IP 55 *IP 56*	(Standard) *(Optional)*
Thermal protection	Without *Customizable*	(Standard) *(Optional)*
Rotation direction	Clockwise *Counter clockwise*	(Standard) *(Optional)*
Service duty	S1	
Vibration level	A	
Balance	Half-key balanced	
Cable glands	1 - M20 × 1.5	
Cooling	IC 411	
Painting color	RAL 7024 *Customizable*	(Standard) *(Optional)*
Regulations	IEC / DIN / ISO / VDE / EN	
Standard	IEC 60034	

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitute	1000 m above sea level

Electrical data		
Output	0.25	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
Rotation speed	1722	RPM @ 50Hz
Rated current	1.60	A (In) @ Δ 50Hz
Starting current	3	×In
Rated torque	1.66	Nm (Mn)
Starting torque	0.5	×Mn
Breakdown torque	1.7	×Mn
Efficiency	IE2 68.5 61.9 50.0	 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.99	@ 100% load

Mechanical data		
Bearings brand	C&U *Customizable*	(Standard) *(Optional)*
Bearings type	6202 2RZ C3 6202 2RZ C3	(DE) (NDE)
Lifetime of bearings		20000 hours
Allowed radial load Allowed axial load		454 N 383 N
Grease type	-	
Lubrication interval of NDE bearing Lubrication interval of DE bearing		- h - h
Moment of inertia	0.00078	Kg*m²
Noise level	65	dB(A)

No. 303 Kangliu Road Kangqiao Town Pudong Shanghai, 201315, China

Tel: +86 (21) 6819 2006, Fax: +86 (21) 5812 9366, Email: info@techtop.net.cn, Website: www.techtop.com